

Product data sheet

RWA K 600 G

Retractable arm drive for installation at windows and doors with fixed connection by means of guide rail



Product features

90° window opening in less than 60 seconds
Powerful drive with high torque
Connection cable easy to replace by means of plug
Integrated status contact for feedback signals
Integrated Syncro module that can operate max. two drives without external control unit
SHEV tested according to EN 12101-2

Application Areas

Smoke and heat extraction and natural ventilation (24 V)
Inward- and outward-opening windows with bottom-hung, top-hung and side-hung leaves
Installation on wooden, PVC or metal windows
Leaf and frame installation
Door installation possible

Product Data Table

Productname	RWA K 600 G
Height	86 mm
Operating voltage	24 V, ± 25 %
Current consumption	1.4 A
Residual ripple (max.)	20 %
Duty rating	30 %
Connection cable length	5 m
Special length of power supply cable	10 m
Cable dimensions	5 Stk. 0.5 mm ²
Temperature range	-5 °C - 75 °C
IP rating / protection rating	IP32 / III
Tandem function	Yes
Syncro function	Yes
Adjustable opening speed (ventilation)	Yes
Additional locking available	Yes
Type of additional locking	Locking drive
Type of stroke shortening	Synchronising unit
End position cut-off extended	Internal path sensor
End position cut-off retracted	Internal path sensor
Overload cut-off	Yes
SHEV tested	Yes
Synchronisation (max.)	2 drives

Bottom-hung window INWARD-opening frame installation	Yes
Bottom-hung window INWARD-opening door leaf installation	Yes
Bottom-hung window OUTWARD-opening frame installation	Yes
Bottom-hung window OUTWARD-opening door leaf installation	Yes
Side-hung window INWARD-opening frame installation	Yes
Side-hung window INWARD-opening door leaf installation	Yes
Side-hung window OUTWARD-opening frame installation	Yes
Side-hung window OUTWARD-opening door leaf installation	Yes
Top-hung window INWARD-opening frame installation	Yes
Top-hung window INWARD-opening door leaf installation	Yes
Top-hung window OUTWARD-opening frame installation	Yes
Top-hung window OUTWARD-opening door leaf installation	Yes

Accessory

Product name

Safety scissor stay no. 35

Safety scissor stay no. 60