

Product data sheet

OL 320

Surface-mounted slimline skylight opener with an opening width of 320 mm



Product data sheet

OL 320

2/3

Product features

Achieves the full opening width of 320 mm for all leaf heights
Opening width can be set
Suitable for leaf weights up to 250 kg
Min. leaf height 400 mm
Min. leaf width 680 mm
Max. leaf width of 3600 mm with three scissor stays
Low space requirement on the door frame and on the leaves
Integrated leaf locking mechanism in the scissor stays guarantees safe locking
Unhinging inhibitor offers additional safety
Lock carrier and additional locks increase safety and air-tightness
Scissor disengagement by pressing the release button facilitates window cleaning from inside and outside
Scissor stays and link arm can be installed from the front
Safety button on the scissor stays shows when the scissor stays engage in the spherical head of the leaf bracket
The leaf bracket is suitable for all overlap heights and materials

Application Areas

Comfortable and daily ventilation of rooms and staircases
For windows with high leaf weights up to max. 250 kg
Inward-opening bottom hung windows
Automation through electric linear drive E 212
Installation on wooden, PVC or metal windows
Frame installation

Product Data Table

Productname	OL 320
Length	436 mm
Öffnungsweite (max.)	320 mm
Casement width (min.)	680 mm
Flügelhöhe (min.)	400 mm
Leaf weight (max.)	250 kg
Adjustable opening width (stroke reduction)	Yes
Leaf lock integrated in the scissor stay	Yes
Scissor stay unhooked by release button	Yes
Unhinging inhibitor	Yes

Accessory

Product name
Gripping and cleaning scissor stay (FPS)