
TAG 690 - VV- 42 (WITH PRIORITY VALVE)




Order designation: TAG 690 - VV - 42 - thread for bottle connection

Example: TAG 690 - VV - 42 - M 10 x 1







After the installation of the fire detection element (glass bulbs \emptyset 5 mm) the energy source (CO $_2$ -bottle) is activated and the pressure released after the connection "A". The connection "B" is vented. The network power connections "PA" and "PB" are blocked.

Short description

→chapter 03, page 41, "Mounting, Operating and Maintenance Instructions TAG"

Operation

medium	CO ₂ compressed air
max. allowed operating pressure	60 bar
test pressure	90 bar
environmental class	according to VdS 2584 Environmental class III, -25 °C to +110 °C
materials	aluminum, niro, brass, steel galvanized, sealings Perbunan
maintenance	once a year (→chapter 03, page 41, "Mounting, Operating and Maintenance Instructions TAG")
VdS-approval number	G 592015
ambient temperature	-25 °C to +60 °C

	l data

The VdS-permission is only valid in connection with the tested glass bulbs and ${\rm CO_2}$ -bottles.

Glass bulbs	CO. bottles wit thread	Tension screw

68° red	▶ W 21,8x1/14	▶ W 21,8 x 1/14
93° green	► M 20x1,5	▶ 1/2" – 20 UNF-IA
141° blue (not VdS)	▶ 1/2" – 20 UNF-IA	► M 18 x 1,5
182° mallow (not VdS)	► M 18x1,5	► M 15 x 1,25
others upon request (not VdS)	▶ M 15x1,25	▶ M 10 x 1
	► M 10x1	

Accessories

Additional	equi	pment (onl	y orde	erwith	DE-I	ora	cket)

→chapter 03, page 39, "Additional Equipment TAG"
→chapter 03, page 39, "Additional Equipment TAG"
→chapter 03, page 39, "Additional Equipment TAG"
→chapter 03, page 39, "Additional Equipment TAG"
→chapter 03, page 39, "Additional Equipment TAG"

Hold

Holder		
fastening rail TAG 40/41/42/43	→chapter 6.2, page 234, "Fastening Rail for TAG"	
holder TAG 40 / 41 / 42 / 43	→chapter 6.2 page 235 "Holder for TAG"	

Date 08.06.2020

Dr.-Köhl-Straße 6 | D-95119 Naila Tel.: +49 9282 48731-0 | +49 9282 48731-29

BSC Technology GmbH

info@jofo.de www.jofo.de