

Product data sheet

E 350 N

Spindle drive in 230 V design with comprehensive console programme



Product features

- Compact design
- Versatile thanks to extensive console range
- Robust design with mechanical load cut-off and IP rating IP65

Application Areas

- Direct opener for natural ventilation (230 V) in the façade and roof area
- Inward- and outward-opening windows with bottom-hung, top-hung and side-hung leaves
- Louvre and roof windows
- Installation on wooden, PVC or metal windows

Product Data Table

Productname	E 350 N
Dimensions (W x H x D)	Stroke + 340 x 40 x 47 mm
Height	40 mm
Depth	47 mm
Possible stroke heights	100 mm, 150 mm, 200 mm, 230 mm, 300 mm, 500 mm, 700 mm, 750 mm, 1000 mm
Opening speed ventilation	5 mm/s
Force of pressure (max.)	750 N
Operating voltage	230 V ± 10 %
Current consumption	0.15 A
Power consumption (max.)	35 W
Duty rating	50 %
Connection cable length	2.5 m
Cable dimensions	3 x 0.75 mm ²
Temperature range	-20 °C - 70 °C
IP rating / protection rating	IP65 / II
Type of stroke shortening	Factory setting
End position cut-off extended	mechanical overload cut-off
End position cut-off retracted	mechanical overload cut-off
Overload cut-off	Yes
Bottom-hung window INWARD-opening frame installation	Yes
Bottom-hung window INWARD-opening door leaf installation	Yes
Bottom-hung window OUTWARD-opening frame installation	Yes

Side-hung window INWARD-opening frame installation	Yes
Side-hung window INWARD-opening door leaf installation	Yes
Side-hung window OUTWARD-opening frame installation	Yes
Top-hung window INWARD-opening frame installation	Yes
Top-hung window INWARD-opening door leaf installation	Yes
Top-hung window OUTWARD-opening frame installation	Yes
OUTWARD-opening roof window	Yes

Accessory

Product name
Console INWARD E 250 NT / E 350 N
Standard console E 250 NT / E 350 N
Stroke limiter 230 V AC
Position feedback for E 350 N
SICHERHEITSSCHERE 35
Safety scissor stay no. 60