

The drives here described are designed for 10 000 ventilation and 1 000 release cycles.

General

connection cable	3 x 1 mm ²
rated current	0,8 A/ 19,2 W
operation mode	S1
input voltage	24 V DC +4/-2 V
EMC	in accordance with 2014/ 30/ EU
colour	aluminum
weight	approx. 1,3 kg with 300 mm stroke
stroke time	approx. 375 mm/ min.
nominal stroke	up to 1 000 mm
nominal force	650 N
protection class	IP 65
ambient temperature	-20 °C to +70 °C

JM-DC(-B)-SYN-650-stroke

connection cable	3 x 1 mm ²
rated current	0,8 A/ 19,2 W
operation mode	S1
input voltage	24 V DC +4/-2 V
EMC	in accordance with 2014/ 30/ EU
colour	aluminum
weight	approx. 1,3 kg with 300 mm stroke
stroke time	approx. 200 mm/ min.
nominal stroke	up to 750 mm
nominal force	1 000 N
protection class	IP 65
ambient temperature	-20 °C to +70 °C

JM-DC(-B)-SYN-1000-stroke

up to 300 mm stroke	1 700 mm
up to 500 mm stroke	1 900 mm
up to 750 mm stroke	2 150 mm
up to 1 000 mm stroke	2 400 mm

Cable lengths

The connection area of the motor supply line is performed in IP 65.